

EDIFIER®

M3600D

M3600D with advanced digital audio technology, low power consumption, built-in high efficiency D class digital amplifier, which can output total 200W RMS.

2.1 active speakers with unique shape and MDF satellite to provide stability and strong impact; 8-inch unit subwoofer can output 130W real power, low frequency can dive to 40Hz; whether it is connected to the computer to enjoy music, or gaming or home theater, M3600D is the best choice of the sound.



200
watts
R.M.S
TOTAL POWER OUTPUT



Features

- THX certificated
- Class D amplifier
- (210mm) 8" subwoofer driver
- DSP digital
- Volume control on the satellite

Specifications

Power Output	: RMS 35W x 2 + 130W
Signal to noise ratio	: R/L: ≥84dB(A) SW: ≥80dB(A)
Frequency response	: 40Hz-20KHz
Input sensitivity	: Line 1: R/L: 600 ±50mV SW: 1300 ±mV Line 2: R/L: 800 ±50mV SW: 1700 ±mV AUX: R/L: 550 ±50mV SW: 1200 ±mV Opt/Coax: R/L: 350 ±50mV SW: 750 ±mV
Input type	: Optical, Coaxial, Line in, AUX
Midrange & bass unit	: 8" (210mm)
Treble unit	: 2 3/4 inches(70mm)
EAN code	: 6923520265961 (Black)



THX and the THX logo are trademarks of THX Ltd., registered in the U.S. and other countries.

Disclaimer: All specifications are subject to change without notice

www.edifier.com

A Passion for Sound