

RLC-830A-IP-Camera-Specifications		
Model	RLC-830A	
Video & Audio	Image Sensor	1/2.7"CMOS Sensor
	Video Resolution	3840 x 2160 (8.0 Megapixels) at 25 frames/sec
	Lens	f=4mm, fixed; f=1.6
	Video Format	H.265
	Field of View	Horizontal: 88°
		Vertical: 46°
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 15 Meters(LED: 2pcs/850nm)
	Color Night Vision	Spotlight: 2pcs/6500K/450 Lumens
Audio	Two-way audio	
Power	PoE	IEEE 802.3af, 48V active
	DC Power	DC 12.0 V □ 1 A, < 12 W
Interface	Power	DC Power port
	System	Reset button
	Ethernet	1*10M/ 100Mbps RJ45
	Storage	Micro SD card slot (max. 256GB)
	Audio	Built-in microphone and speaker
Pan & Tilt	Pan &Tilt	Pan: 355°, Tilt: 0°~90°
	Pan Speed	12°-90°/s (The speed can be set.)
	Tilt Speed	8°-60°/s (The speed can be set.)
	Preset	32
	Auto Tracking	Available
Software Features	Frame Rate	Mainstream: 2fps - 25fps (Default: 25fps)
		Substream: 4fps - 15fps (Default: 10fps)
	Code Rate	Mainstream: 4096Kbps -8192Kbps (default: 6144Kbps)
		Substream: 64Kbps -512Kbps (default: 256Kbps)
	Compatible Browsers	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/ person detection/ vehicle detection/ pet detection (beta version)
	Record Mode	Motion activated recording (default); scheduled recording; recording 24/7
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximum User Access	20 users (1 admin account and 19 user accounts); 12 simultaneous video streams (10 substreams and 2 mainstreams)	
Work with	Google Assistant	
Working Environment	Temperature	Operating Temperature: -10°C~+50°C (14°F~122°F)
	Humidity	Operating Humidity: 10% ~ 90%
	Waterproof	Support
Size & Weight	Dimension	228*110*147mm
	Weight	1.2KG
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Δήλωση συμμόρφωσης ΕΕ (GR)

Manufacturer: REOLINK INNOVATION LIMITED

Address: FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET MONG KOK KL HONG KONG

Αυτή η δήλωση συμμόρφωσης εκδίδεται με αποκλειστική ευθύνη του κατασκευαστή και ανήκει στο ακόλουθο προϊόν:

Τύπος Προϊόντος: IP Camera

Μοντέλο: RLC-830A

Το αντικείμενο της δήλωσης που περιγράφεται παραπάνω είναι σύμφωνο με τη σχετική Νομοθεσία εναρμόνισης της Ένωσης:

- EMC Directive: 2014/30/EU
- LVD: 2014/35/EU
- RoHS Directive: 2011/65/EU&(EU)2015/863

Έχουν εφαρμοστεί τα ακόλουθα εναρμονισμένα πρότυπα και τεχνικές προδιαγραφές:

EMC	EN 55032:2015/A11:2020 EN IEC 61000-3-2:2019 EN 61000-3-3:2013/A1:2019 EN 55035:2017/A11:2020
LVD	EN IEC 62368-1:2020+A11:2020
RoHS	IEC 62321-3-1:2013/ IEC 62321-5:2013 IEC 62321-4:2013+A1:2017 IEC 62321-7-2:2017/ IEC 62321-6:2015 IEC 62321-7-1:2015/ IEC 62321-8:2017

Υπογράφηκε για και για λογαριασμό του: REOLINK INNOVATION LIMITED

Τόπος έκδοσης: Hong Kong

Ημερομηνία έκδοσης: 28-12-2022

Όνομα: Wang aijun

Θέση: Τεχνικός διευθυντής

Υπογραφή:

Wang aijun

EU Declaration of Conformity (EN)

Manufacturer: REOLINK INNOVATION LIMITED
Address: FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77FA YUEN
STREET MONG KOK KL HONG KONG

This declaration of conformity is issued under the sole responsibility of the manufacturer and belongs to the following product:

Product Type: IP Camera

Model: RLC-830A

The object of the declaration described above is in conformity with the relevant Union harmonization legislation:

- EMC Directive: 2014/30/EU
- LVD: 2014/35/EU
- RoHS Directive: 2011/65/EU&(EU)2015/863

The following harmonized standards and technical specifications have been applied:

EMC	EN 55032:2015/A11:2020 EN IEC 61000-3-2:2019 EN 61000-3-3:2013/A1:2019 EN 55035:2017/A11:2020
LVD	EN IEC 62368-1:2020+A11:2020
RoHS	IEC 62321-3-1:2013/ IEC 62321-5:2013 IEC 62321-4:2013+A1:2017 IEC 62321-7-2:2017/ IEC 62321-6:2015 IEC 62321-7-1:2015/ IEC 62321-8:2017

Signed for and on behalf of: REOLINK INNOVATION LIMITED

Place of issue: Hong Kong
Date of issue: 28-12-2022
Name: Wang aijun
Position: Technical Director
Signature:

Wang aijun